

[Foot Mounted Planetary Gearbox](#)

reduction gearbox ,Foot Mounted Planetary Reducer Model Foot Mounted Series Replace for Brevini ED, ET, EQ, EM, EC and EL series Bonfiglioli 300 series Dinamicoil RE, RA series Reggiane Riduttori RR series Ratio 3.4-5000 Output Torque 1000-450000N.m OverviewThe installation and overall dimension of planetary gearboxes are strictly designed in accordance with Italy and American manufacturers, so they can be completely interchangeable with Brevini ED, ET, EQ, EM, EC and EL series, Bonfiglioli 300 series and Dinamicoil RE, RA series on performance and connection dimensions. They are the ideal product to replace those Italian products. ConfigurationMounting solution: flange mounted, foot mounted, shaft mounted Features:- Torque Range: 1000 ... 1.100.000 Nm - Transmissible Mechanical Power: up to 450 kW - Gear Ratios: $i=3,4 \dots 5.000$ - Gear Unit Versions Right angle (with a spiral bevel gear set)- Output ConfigurationFoot and flange mounted- Output shaft: solid with key, splined, splined hollow, hollow with shrink disc - Input ConfigurationsFlanged axial piston hydraulic motorsHydraulic orbit motorsIEC and Nema motor adaptorsSolid input shaft - Hydraulic BrakeHydraulically released parking brake on request - Electric Brake: DC and AC type Model Ratio (i) Output Torque (Nm) Download 300 3.4-2700 1000 Technical data ED300 301 3.4-2700 1750 Technical data ED301 303 3.6-2800 2500 Technical data ED303 304 3.6-2500 3500 Technical data ED304 305 3.6-2800 5000 Technical data ED305 306 3.6-2900 8500 Technical data ED306 307 3.4-2500 12500 Technical data ED307 309 3.4-2500 18500 Technical data ED309 310 4-5000 25000 Technical data ED310 311 4-5000 35000 Technical data ED311 313 4-5000 50000 Technical data ED313 314 4-5000 65000 Technical data ED314 315 4-5000 80000 Technical data ED315 316 4.4-5000 105000 Technical data ED316 317 4-5000 150000 Technical data ED317 318 4.4-5000 200000 Technical data ED318 319 4.8-5000 300000 Technical data ED319 321 4.4-5000 450000 Technical data ED321



[Undercarriage](#), [Steel Tracked Undercarriage](#), [Rubber Tracked Undercarriage](#), [Hydraulic Pump](#),

NINGBO BONNY HYDRAULICS TRANSMISSION CO., LTD

Add: No. 36, the third road of Dagang, Beilun, Ningbo, Zhejiang, China

Contact: Cathy Hsu

Tel: 574-86879210

Fax: 574-86877981

E-mail: sales@bonnyhydraulic.com

WebSite: <http://www.bonnyhydraulic.com>
